

TECHNICAL DATASHEET

ARMOURCURE WBH SERIES

Type	Water-based PUD Hybrid
Form Supplied	Dispersion in Water
Uses	Economical, hard-wearing sealer for concrete and block paving

Properties*	Value	Unit of Measurement
Solids Content	20	%
Viscosity at 25°C	60	mPa.s
pH Value	8-7	-

Other Properties*		Method
Colour	Translucent	-
Specific Gravity (25/25°C)	1.01	-
Flash Point	>100	°C Abel
Elongation at break	200	%
Abrasion Resistance (Taber)	150mg wt. loss (Wheel CS17/1000g load /1000 rev)	

Application Rate 15m² per litre

Properties Armourcure WBH is an environmentally friendly alternative to solvent systems and can be used for sealing a variety of substrates including block paving and various concrete floors. In particular Armourcure WBH offers both good sand stabilisation and wear resistance when used on new or refurbished concrete and block paving.
 Armourcure WBH is available in 200L and 25L

Storage and Shelf Life Store out of direct sunlight. Protect from Frost. Wherever possible store in original unopened containers until needed. Shelf life is 12 months from date of manufacture.

Safety Information Armourcure WBH has been classified as a non hazardous substance but users are encouraged to refer to the Material Safety Data Sheet corresponding to this product. Precautions should be taken to ensure that gloves and safety glasses are worn when handling this product.

***Note:** Information is given in this data sheet, in good faith, to assist users with the identification of products for various purposes. It is recommended that users consult the full product Technical Data Sheet for more specific information and must undertake their own trials to establish suitability as no liability can be accepted by Isedio should materials or methods prove to be unsuitable for such purposes.